

950-6

Mini Door Control Console



- **Compact, Desktop Design**
- **Controls 6 Doors**
- **Controls 2 Locks for Each Door**

A cost-effective and space-efficient solution for smaller facilities and temporary installations. It is a great alternative for jobs that do not require the comprehensive solution provided by the AES 900 Rack system.

This desktop console monitors and controls six (6) doors. Each door includes two (2) locks: an emergency lock; and an access lock. Both locks must be released for the door to open. Indicators on the console display the status of the emergency lock, and the door position (open/closed).

AES Corporation

Call 1-800-237-6387

285 Newbury Street • Peabody, MA 01960 USA

Tel +1-978-535-7310 • Fax +1-978-535-7313

<http://www.aes-security.com>

Copyright AES Corporation 2006—All Rights Reserved
950-6.P 04/25/06

950-6 Mini Door Control Console

Size

- 11"W x 8.5"D x 3.25"H (28 x 21.5 x 8.3 cm) (approx)

Voltage:

- 24VDC; use AES 726, 727 or 780 Power Supply and Relay Controls, and Battery Backup

Indicators, LED's:

- 6 - Lock Status,
- 6 - Door Status
- 1 - Power

Switches:

- 6 - Toggles, Access/Secure Emergency Locks
- 6 - Push Button, Strike Locks

Audible Annunciator:

- Buzzer / Door Open
- May be deactivated using 6 position DIP switch

Connector:

- Barrier Block

Case:

- Slope Front, Desktop Style; Steel, Hardwood Endcaps

Toggle Switch Operation:

- Down "SECURE" Position - Latches emergency lock
- Up "ACCESS" Position - Releases emergency lock
- PUSH BUTTON SWITCH OPERATION:
Push - Releases access strike lock

Status Indicators:

- Amber "LOCK" Lamp - Indicates emergency lock is not activated, confirming that door can be opened
- Red "DOOR" Lamp - Indicates that door is open

Audible Indicators:

- An audible warning sounds whenever a door is opened. This feature can be activated or deactivated on a door by door basis.

Ordering:

- AES 950-6 Mini Door Control Console

See Also: AES Access Control Power Supplies, models 726, 727 and 780.

950-6 Mini Door Control Console Specifications



For more information

Call 800-237-6387 / 978-535-7310

285 Newbury Street • Peabody, MA 01960 USA

Tel +1-978-535-7310 • Fax +1-978-535-7313

Copyright AES Corporation 2006—All Rights Reserved
950-6.P 04/25/06

