

726-24DC/3A



Power Supply with Charger for Access Control

**A Proven Performer,
Used Around the
World in All Types of
Environments**



Rugged, Reliable, Proven Performance

- **26.5VDC Output**
- **110/220V, 50-60 Hz Input**
- **3 Amps Continuous Duty**
- **80 Amps Intermittent**
- **4 - DPDT Relay Outputs**
- **Battery Backup***

** Battery Pack Sold Separately,*

- 24VDC Power, Battery Charger, Four (4) Control Relays and Battery Backup* All in One Box.
- Locking Steel Case
- Can be used in a secured area or remotely
- A battery pack* can be safely stored inside the case

AES Corporation

Call **1-800-237-6387**

285 Newbury Street • Peabody, MA 01960 USA

Tel +1-978-535-7310 • Fax +1-978-535-7313

<http://www.aes-security.com>

Copyright AES Corporation 2006—All Rights Reserved

726-24DC.P 04/25/06



4.726-24DC (1/2)

Model 726-24 DC/3A Power Supply

- **Input Power:** 110/220V, 50-60 Hz, jumper selectable
- **Output Power:** 26.5VDC, 3 amps Continuous, 80 amps Intermittent
- **Relays:** 4 - DPDT, contacts rated at 10 amps (res)
Controls up to 4 electric locks, one relay per lock
- **Protection:** Fused Secondary;
Circuit Breaker on front of case for AC input side of supply.
- **Applications:** AES 900 Door Control System, other 24VDC Systems
- **Enclosure:** Steel; key lock
- **Size:** 14 x 14.25 x 6 inches (36 x 37 x 15 cm)
- **Weight:** 42 pounds; 19 kilograms
- **Indicator:** Light for AC Input
- **Terminals:** Barrier Blocks
- **Battery:** 24V, 7 AH, lead acid gel type, 80 Amp rating
(order battery pack separately, p/n 726-HDB)
- **Ordering:** Power Supply Part Number 726-24DC/3A
24V 7AH Battery Pack, Part Number 726-HDB
(order separately)

726-24DC/3A Power Supply Specifications



For more information

Call 800-237-6387 / 978-535-7310

285 Newbury Street • Peabody, MA 01960 USA

Tel +1-978-535-7310 • Fax +1-978-535-7313

Copyright AES Corporation 2006—All Rights Reserved
726-24DC.P 04/25/06

